

Professionele lamineermachines  
enkel- en dubbelzijdig  
voor **drukwerken van hoge offset volumes**



Triton B1  
Portrait

Triton B1  
Landscape

Triton B1 DS  
(Double side)

Polaris

<b>Papersize Min.</b>	205mm x 297mm	205mm x 297mm	205mm x 297mm	210mm x 297mm
<b>Papersize Max.</b>	760mm x 750mm	760mm x 1050mm	760mm x 1050mm	760mm x 1050mm
<b>Paperweight</b>	115gr/m <sup>2</sup> - 450gr/m <sup>2</sup>	115gr/m <sup>2</sup> - 450gr/m <sup>2</sup>	115gr/m <sup>2</sup> - 450gr/m <sup>2</sup>	90gr/m <sup>2</sup> - 450gr/m <sup>2</sup>
<b>Film range</b>	24μ - 42μ	24μ - 42μ	24μ - 42μ	24μ - 42μ
<b>Feeder</b>	Hight pile feeder	Hight pile feeder	Hight pile feeder	Hight pile feeder
<b>Stack Height</b>	80cm	80cm	80cm	80cm
<b>Serial Output</b>	Jogger	Jogger	Jogger	Jogger
<b>Option Output</b>	Pallet Stacker	Pallet Stacker	Pallet Stacker	Pallet Stacker
<b>Speed</b>	40m./min.	40m./min.	40m./min. - 2 sided 35m/ min.	50m./min.
<b>Heating system</b>	Electrical Bands	Electrical Bands	Electrical Bands	Sealed Oil Filled Roller
<b>Paper separation</b>	Pneumatique	Pneumatique	Pneumatique	Pneumatique
<b>Electrical requirements</b>	380 volts	380 volts	380 volts	380 volts
<b>Air supply</b>	Compresseur 8 Bar	Compresseur 8 Bar	Compresseur 10 Bar	Compresseur 10 Bar
<b>Spécifications</b>	PLC Controlled - Touchscreen. Pneumatique Adjustable Feed Roller - Total and batch counter Integrated Perforating Wheel - Heated Steel Top Roller - Rubber Nip Roller Decurl bar which can be adjusted on the run.			
<b>Options</b>	Pre-loader	Pre-loader	Pre-loader	Pre-loader Extented Feed Table 1050mm

  
**PRINTEMAT**  
A clearer vision for the perfect finish



  
**PRINTEMAT**  
A clearer vision for the perfect finish

Printemat sprl  
Parc Industriel de Noville-les-Bois  
Rue Ernest Montellier, 32 · B-5380 Fernelmont (Namur)  
Tél: +32 (0)81 46 23 30 · Fax: +32 (0)81 46 23 31  
E-Mail: [printemat@skynet.be](mailto:printemat@skynet.be) · [www.printemat-group.be](http://www.printemat-group.be)  
Exclusive Distributor For Benelux & France



WORLD WIDE N°1  
IN THERMAL LAMINATING



Professionele lamineermachines  
enkel- en dubbelzijdig voor **digitaal drukwerken**  
alsook voor **drukwerken van kleine offset volumes**



Neptune

Europa

Europa EL  
(Embossing)

Europa PB  
(Double side)

<b>Papersize Min.</b>	205mm x 297mm	205mm x 220mm	205mm x 220mm	205mm x 220mm
<b>Papersize Max.</b>	360mm x 540mm	540mm x 740mm	540mm x 740mm	540mm x 740mm
<b>Paperweight</b>	115gr/m <sup>2</sup> - 350gr/m <sup>2</sup>	115gr/m <sup>2</sup> - 350gr/m <sup>2</sup>	115gr/m <sup>2</sup> - 350gr/m <sup>2</sup>	115gr/m <sup>2</sup> - 350gr/m <sup>2</sup>
<b>Film range</b>	24μ - 42μ	24μ - 42μ	24μ - 42μ	24μ - 42μ
<b>Feeder</b>	Hight pile feeder	Hight pile feeder	Hight pile feeder	Hight pile feeder
<b>Stack Height</b>	60cm	80cm	80cm	80cm
<b>Serial Output</b>	Collection tray	Collection tray	Collection tray	Collection tray
<b>Option Output</b>	Jogger	Jogger of Pallet Stacker	Jogger of Pallet Stacker	Jogger of Pallet Stacker
<b>Speed</b>	15m./min.	20m. /min.	20m. /min.	20m. /min.
<b>Heating system</b>	Electrical	Electrical	Electrical	Electrical
<b>Paper separation</b>	Pneumatique	Pneumatique	Pneumatique	Pneumatique
<b>Electrical requirements</b>	380 volts	380 volts	380 volts	380 volts
<b>Air supply</b>	Compressor 6 Bar	Compressor 7 Bar	Compressor 7 Bar	Compressor 8 Bar
<b>Spécifications</b>	PLC Controlled - Touchscreen. Pneumatique Adjustable Feed Roller - Total and batch counter Integrated Perforating Wheel - Heated Steel Top Roller - Rubber Nip Roller Decurl bar which can be adjusted on the run.			
<b>Options</b>	Extented Feed Table 960mm Rewinder For Application Foil	Extented Feed Table 1050mm Rewinder For Application Foil	Extented Feed Table 1050mm	Extented Feed Table 1050mm

Professionele lamineermachines  
enkel- en dubbelzijdig  
voor **drukwerken van gemiddelde offset volumes**



Jupiter 35

Jupiter 35  
Landscape

Jupiter DS  
(Double side)

Proteus

<b>Papersize Min.</b>	205mm x 220mm	205mm x 220mm	205mm x 220mm	225mm x 320mm
<b>Papersize Max.</b>	540mm x 740mm	740mm x 740mm	540mm x 740mm	720mm x 1020mm
<b>Paperweight</b>	115gr/m <sup>2</sup> - 450gr/m <sup>2</sup>	115gr/m <sup>2</sup> - 450gr/m <sup>2</sup>	115gr/m <sup>2</sup> - 450gr/m <sup>2</sup>	90gr/m <sup>2</sup> - 450gr/m <sup>2</sup>
<b>Film range</b>	24μ - 42μ	24μ - 42μ	24μ - 42μ	24μ - 42μ
<b>Feeder</b>	Hight pile feeder	Hight pile feeder	Hight pile feeder	Hight pile feeder
<b>Stack Height</b>	80cm	80cm	80cm	80cm
<b>Serial Output</b>	Jogger	Jogger	Jogger	Jogger
<b>Option Output</b>	Pallet Stacker	Pallet Stacker	Pallet Stacker	Pallet Stacker
<b>Speed</b>	35m./min.	35m./min.	35m./min. - 2 sided = 25m./min.	35m./min.
<b>Heating system</b>	Sealed Oil Filled Roller	Sealed Oil Filled Roller	Electrical	Sealed Oil Filled Roller
<b>Paper separation</b>	Pneumatique	Pneumatique	Pneumatique	Pneumatique
<b>Electrical requirements</b>	380 volts	380 volts	380 volts	380 volts
<b>Air supply</b>	Compresseur 7 Bar	Compresseur 7 Bar	Compresseur 8 Bar	Compresseur 8 Bar
<b>Spécifications</b>	PLC Controlled - Touchscreen. Pneumatique Adjustable Feed Roller - Total and batch counter Integrated Perforating Wheel - Heated Steel Top Roller - Rubber Nip Roller Decurl bar which can be adjusted on the run.			
<b>Options</b>				

  
**PRINTEMAT**  
A clearer vision for the perfect finish

**WORLD WIDE N°1  
IN THERMAL LAMINATING**



Ontdek eveneens ons gamma laminating films  
OPP **Superstick**® en **SofTouch**® die perfect passen bij alle numerieke drukwerken

Onze **Superstic**® films garanderen een perfecte adhesie,  
zelfs op de delikaatste drukwerken!

Dank zij de **Europees gerenomeerde en robuuste lamineermachines van D&K**, zal u een meerwaarde hebben op uw inkomsten alsook op uw drukwerken, dit met een grootse flexibiliteit. Onze verschillende referenties en de kwaliteit van onze naverkoopdienst zijn uw garantie voor een return op uw investering op lange termijn.